AC / DC CURRENT METER

Model No.	AA-24T	AA-24T-1	DA-24T	DA-24T-1	DA-24T-2
Measuring Range	0~5A	0~20mA	0~5A	0~200mA	4~20mA
Type	AC Current Meter		DC Current Meter		
Input Voltage	AC Voltage		DC Voltage		
Power Supply	110V / 220VAC , 50/60Hz				
Display Range	0~1999, 25.4mm 7-Segment Red LED				
Converting Method	Dual Slope A/D Converter				
Accuracy	±0.2% of F.S.				
Response Time	2 seconds				
Dielectric Strength	2.5KV/1 min.				
Isolation Strength	100MΩ/500VDC				
Circumstance	-20°C~ +60°C; 35~85%RH				

Dimension: W96xH48mm
Panel Cutout: W92xH45mm

AA-24T **DA-24T**

SM-20 Tachometer & Line speed Meter

Model No.	SM-20	SM-20S
Transmitter	None	4~20mA
Alarm Output	Relay	None
Control Output	Hi / Lo	None
Power Supply	90 ~ 265VAC, 50/60Hz	
Current Consumption	5VA max.	
DC Output	12V / 100mA Max.	
Input Method	NPN	
Response Time	Ton=0.1ms~99.9mSeconds settable	
Pules Per Revolution (PPR)	1~999PPR Settable	
Diameter	1~999mm settable (Line speed meter available only)	
Memory Method	EEPROM	
ESD strength	Over 8KV	
Dielectric Strength	Over 2.5KV / 1 min., Between Power & each other terminal	
Isolation Strength	Over 100MΩ /500VDC, Between Power & each other terminal	
Operating Circumstance	-20°C ~ +60°C; 35~85%RH	

- Multifunction for Tachometer & Line speed Meter & Duty Meter
- Pulses per revolution settable
- Sampling time auto tuning
- Decimal point and limit of Alarm are settable

Dimension: W96xH48mm
Panel Cutout: W92xH45mm