

K/type Single / Dual Thermometer

- 3 1/2 digit liquid crystal display (LCD) with 0.1° high resolution
Handheld lightweight design, with Offset adjust, Data hold, MAX hold
- **305**: Single Thermocouple Input
- **307**: Dual Thermocouple with differential temperature (T1-T2)
°C or °F switchable on front panel, Front panel Offset adjustment
- Measuring range: -50 ~ 1300°C or -58 ~ 1999°F
- Accuracy: For operating temperatures over the range 18°C to 28°C for 1 year, not including thermocouple error.
± (0.3% rdg + 1°C) -50°C to 1000°C
± (0.5% rdg + 1°C) 1000°C to 1300°C
± (0.3% rdg + 2°F) -58°F to 1999°F
- Battery: one 9V battery (NEDA 1604), 200 hours typical with carbon zinc battery
- Dimensions(mm) : 147(H) x 70 (W) x 39 (D), weight 7.4oz (210g)



K/J - Type Dual Input Thermometer

Model: 502 (Dual), 503 (Single)

Features:

- 4 3/4 digital 25000 counts with dual display
- K/J types thermocouple selection input
- MAX/MIN with elapsed time, Average, REL, HOLD function
- RECALL function (Model: 503)
- High accurate with 0.1%
- With Hi/Lo setting (Model: 502), Hi/Lo RECALL (Model: 503)
- °C / °F user-selective
- TIME setting, REL setting
- Low battery indication: The "BAT" is played when the battery voltage drops below the operating level.
- Accuracy specification does not include Temperature Probe's accuracy.
- J-type Range: -200 to 1050°C ; -328 to 1922°F
- K-type Range: -200 to 1370°C ; -328 to 2498°F

K/J/T/E-Type Dual Input & Output Thermometer & Calibrator

Model: 513

Features:

- 3 1/2 digital with high resolution
- Display back-light feature
- K/J/T/E-types thermocouple selection
- Dual Input & HOLD function
- High accurate with 0.1%
- Auto range 0.1 / 1°
- °C / °F user-selective
- Auto power off function

Application:

Greenhouse, Weather monitoring, Labs, Workshops...



Single/Dual Input RTD Thermometer

Model: 805

Model: 805U (USB+Adapter)

Model: 805W (Wireless)

Model: 805UW (USB+Adapter+Wireless)



For Model: 805U/805UW



Model: 804

Model: 804U (USB+Adapter)

Model: 804W (Wireless)

Model: 804UW (USB+Adapter+Wireless)



For Model: 804U/804UW



805



804

Features:

- USB Port provides excellent user interface (804U/804UW/805U/805UW)
- DC 12V adapter (804U/804UW/805U/805UW)
- Wireless two ways transmission (804U/804UW/805W/805UW)
- 805-series for Pt100 ohm single input & 804-series for Dual Pt100 input
- Pt3916/Pt3926/Pt385 RTD standard
- °C/°F user-selective
- MAX/MIN with elapsed time, AVG, REL, REL RECALL, Hi RECALL, Lo RECALL, HOLD function
- TIME setting, REL setting
- Warning beeper with Hi/Lo setting
- Resolution 0.1°C to 0.2°F
- According to temperature standard ITS-90

(804U/804UW/805U/805UW)

Accessories: USB cable.

12VDC Adaptor.(Option)

(804U/804UW/805W/805UW)

WIRELESS Features:

Frequency range: 910~920MHz.

Low current consumption less than 1mA.

The transmitting distance can reach 25M without magnetic interference.